MATERIAL SAFETY DATA SHEET This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFAC	CTUF	RER'S INFORMATIC	DN				
NFPA Rating: Health-1; Flammability-0; Reactivity-0; Special HMIS Rating: Health-1; Flammability-0; Reactivity-0; Personal Protection-B							
Manufacturer's Name: Amrep, Inc	DOT Hazard Classification:						
	Identity (trade name as used on label):						
Address: Marietta, GA 30062		MISTY WHITE GUARD SUPREME WITH PTFE					
Date Prepared: 09-05-97 Prepared By: ES/DL/IB	MSDS Number: RL 724 Revision - 6						
Information Calls: (770)422-2071	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					ST DATA	
Emergency Response Number: 1-800-255-3924							
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES CAS Number SARA OSHA PEL ACGIH Carcinogen							
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
USP WHITE MINERAL OIL		8042-47-5	No	5mg/M3	5mg/M3	d	
				For oil mist	For oil mist		
CALCIUM CARBONATE		1317-65-3	No	5mg/M3	5mg/M3	d	
				Dust	Dust		
ALUMINUM SOAP		68647-58-5	No	N/E	N/E	d	
ZINC OXIDE		1314-13-2	No	N/D	N/D	d	
POLYISOBUTYLENE		9003-27-4	No	5mg/M3	5mg/M3	d	
		0000 2.		0	For oil mist	ũ	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): .89							
Vapor Pressure: PSIG @ 70°F (Aerosols): N/A Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/D							
	Evaporation Rate (ethyl ether = 1): N/A						
Solubility in Water: Negligible		r Reactive: N/D					
Appearance and Odor: White gel with oil odor.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME Auto Ignition Temperature Flammability Limits in Air by % in Volume:							
PROJECTION TEST (aerosols) N/A N/D							
	SPECIAL FIRE FIGHTING PROCEDURES: Use water spray only to cool						
	containers. Water stream may spread fire. Firefighters may need to wear self-						
Unusual Fire & Explosion Hazards: Will not flash spontaneously; may ignite if exposed to open flame. Do not cut or weld on containers.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizers Conditions to Avoid: None							
Hazardous Decomposition Products: Oxides of carbon, aluminum, calcium and zinc.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: []INHALATION [X]INGESTION [X]SKIN ABSORPTION [X]EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Not expected to be acutely toxic by inhalation based on data from components. Breathing petroleum oil mist at concentration in air that exceeds the							
recommended exposure standard can cause respiratory irritation or discomfort.							
Eye Contact: May cause eye irritation by abrasion based on data from Skin Contact: May cause skin irritation by abrasion based on data from							
components.	components. Primary hazard associated with grease in high pressure gun. If						
	injected under the skin, necrosis could result.						
Ingestion: May cause irritation, nausea or diarrhea. Possible aspiration hazard.							
CHRONIC EFFECTS: None known.							
Medical Conditions Generally Aggravated by Exposure: None known.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Immediately flush eyes with water for a minimum of 15 minutes occasionally lifting lower & upper lids. If film or irritation persists, seek medical							
attention.							
Skin Contact: Wash exposed portions with soap & water. If injected under the skin, get medical attention immediately. Launder soiled clothing before reuse.							
Inhalation: If respiratory discomfort or irritation occurs, move person to fresh air. If breathing has stopped, give artificial respiration & get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink large quantities of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): Organic vapor respirator. Firefighters should wear self-contained positive pressure breathing apparatus.							
Protective Gloves: Nitrile or neoprene, oil resistant. Eye Protection: Safety glasses or chemical goggles.							
Ventilation Requirements: Maintain local or dilution ventilation to keep air conc. below PEL/TLV. Request assistance of safety & industrial hygiene personnel to determine air concentration.							
Other Protective Clothing & Equipment: Oil resistant apron.							
Hygienic Work Practices: Do not wear oil soaked clothing. Wash after handling.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb on fire resistant absorbent. Place in properly labeled non-leaking containers for proper disposal.							
Waste Disposal Methods: Dispose of in accordance with all current local, state and federal regulations.							
Precautions To Be Taken In Handling & Storage: Keep away from flames, sparks or hot surfaces. See also section 3. Keep containers closed. Shelf life 1 year.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Do not wear contaminated clothing. Wash skin thoroughly after handling.							
Clean empty containers properly. We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.							

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

